



Front Elevation and Profile Shown With Anti-Ligature TRV Kit & Shroud 9213-63 in Position

Type:
DeepClean IP3x Compliant Anti-Ligature
Grille LST Radiator

Model: Gradient Top - Floor Mounted

Manufacture:
1.5mm - 3mm Mild Steel (Depending on
Installation Environment)
10mm Radius Corners
Full Height Front Access Door Available
(Depending on Installation Environment
- Pat. No. 2 410 544)
IP3x Test (To BS EN 60529) Compliant
Guard Grille, Incorporating 2mm holes at
4mm Centres in Triangular Pitch
Formation. Complies with Home Office
Police Buildings Design Guide – Custody,
July 2009, section PD3.02.14

All Apertures:
Cut-Outs Programmed into Manufacture
28mm Valve Knockouts Available

Sizes:
Single Casing Length 500mm - 2000mm.
Single Casing Height 580mm - 995mm
Bespoke Solutions Available

Finish:
Polyester PowderCoated RAL 9003 As
Standard With Patented BioCote® Anti-
Microbial Agent. Other Colours Available.

Emitter: QRL Hi-Lo round top radiator.

Valve Options:
Internal TRV Kit 9210-13
External TRV Kit 9231-41
Remote Sensing TRV Kit 7463-41
Anti-Ligature TRV Kit & Shroud 9213-63
"RotaRad" Rotating Valve Kit

Fixings:
All Fixings Internal
8mm PinHex Door Locks (*Other Locks Also
Available*)

Please note: The grille size used in the IP3x anti-ligature radiator guard can inhibit the convection process. Therefore Contour cannot guarantee that the casing will not exceed a surface temperature of 43 degrees Centigrade.

Contour Casings Ltd
Stafford Park 15
Telford
TF3 3BB
Tel: 01952 290498
Email: Sales@contourcasings.co.uk
Web: www.contourcasings.co.uk